

TENANT STORAGE LOCKERS



MODULAR WIRE MESH STORAGE LOCKERS

- ❖ Offers full visibility, light diffusion and air flow
- ❖ Quick assembly using fully framed panels
- ❖ Open mesh allows optimum sprinkler coverage for fire code compliance

FLEXIBLE DESIGN

- ❖ Both standard and custom sizes available
- ❖ Welded or woven mesh, expanded metal and solid sheet metal available
- ❖ Can be fabricated in single / double / triple tier lockers
- ❖ Shelves are optional on all lockers
- ❖ Optional mesh ceilings
- ❖ Custom finishes for harsh environments

APPLICATIONS

- ❖ Condo & apartment tenant storage
- ❖ Retail storage
- ❖ Military lockers
- ❖ Colocation equipment storage
- ❖ Livestock and equestrian containment / feed storage



PROGUARD SERIES TENANT STORAGE LOCKERS

PRODUCT SPECIFICATIONS:

WALL PANELS: Manufactured with our standard 10 gauge 2" square welded wire mesh which is securely welded into a 1 ¼" x 1 ¼" x 1/8" steel angle frame. Each corner is welded to ensure optimal durability.

DOOR PANELS: Single, double, and triple tier units are framed with a 1 ¼" x 1 ¼" x 1/8" steel angle. Single tier doors have two diagonal stiffener bars of ¼" x ¾" flat welded to the door frame and wire mesh. Double tier doors are manufactured using one diagonal flat bar. All doors are constructed with 2 ½" x 3" welded fixed pin hinges, door strikes and padlock hasps. Door locks are available for an additional charge.

BACK PANELS: Manufactured in an 18 gauge pre-galvanized steel sheet metal with slotted holes punched on both sides for easy installation.

ROOF PANELS: Optional roof panels are available for all configurations. Constructed of 10 gauge 2" square welded wire mesh which is securely welded to a 1 ¼" x 1 ¼" x 1/8" steel angle frame. All roof panels have slotted holes punched to allow for easy installation.

HARDWARE: All locker configurations use standard grade ¼" zinc plated carriage bolts with a KEP nuts for a lock tight fit.

FINISHES:

- 1. Standard Paint:** Electro-statically shop allied air-dried alkyd base enamel paint (gray or black). Custom colors are available for a nominal fee.
- 2. Powder coat:** Electro statically shop applied polyester powder coat, oven cured.
- 3. Hot-dip galvanized:** Hot-dip zinc galvanizing after fabrication.



FREE DESIGN

We provide free design assistance to maximize your tenant storage needs. Speak with one of sales representatives or distributors for more information.

HOW TO ORDER:


Please submit the quantity and type of lockers (single / double / triple tier) along with the required finish.

- ❖ Note: Unit sizes, height and if roof panels are required.
- ❖ Any special requirements please indicate.
- ❖ Note if there are obstructions

Fax or email a sketch / plan view of the room to one of our experienced sales representatives at:

(732)-661-2003 fax
sales@newarkwireworks.com

EXAMPLE SKETCH:



INSTALLATION AVAILABLE

Newark Wire Works Inc.
1059 King Georges Post Rd.
Edison, NJ 08837
(732)-661-2001 main
(732)-661-2003 fax
Sales@newarkwirreworks.com

Distributed by:

Follow us:



