

Proguard Wire Mesh Partitions



Proguard Series Wire Mesh Partition Specifications				
Mesh:				
Туре:		10ga. (.135) plain steel, 2" x 2" square welded wire mesh. Mesh is welded to angle iron frame.		
Wall panels :				
Vertical frame :		1 1/4" x 1 1/4" x 1/8" angle		
Horizontal frame :		1 1/4" x 1 1/4" x 1/8" angle		
Mid-rail :		1 1/4" x 1/8" flat iron		
Hinged Doors:				
Vertical frame :		1 1/4" x 1 1/4" x 1/8" angle		
Horizontal frame :		1 1/4" x 1 1/4" x 1/8" angle		
Mid-rail :		1 1/4" x 1/8" flat iron		
Lock:		Marks 3700 series		
Sliding gates:				
Vertical frame :		1 1/4" x 1 1/4" x 1/8" angle		
Horizontal frame :		1 1/4" x 1 1/4" x 1/8" angle		
Mid-rail :		1 1/4" x 1/8" flat iron		
Lock:		Marks 3700 series		
Larger height partition stiffening posts:				
Tube:	2" x 2" x 14ga. steel tube		Heights:	7'-0" - 18'- 0"
Tube:	2" x 3" x 14ga. steel tube		Heights:	18'- 1" - 24'- 0"
Tube:	2" x 4" x 14ga. steel tube		Heights:	24'-1"- 30'-0"
Tube:	2" x 6" x 14ga. steel tube		Heights:	30'-1"- 40'-0"
Line Posts:				
Standard:		3"x1 1/2" x 11ga. Steel channel with bolt holes to match panel & welded base plate w/ 4 holes for tek screws into access floor		
above 8ft:		3"x3"x11ga. Steel square tube with 8"x8"x1/4" welded base plate with 4 holes with 3/8" diameter wedge anchors into concrete floor		

Newark Wire Works Inc. 1059 King Georges Post Rd. Edison, NJ 08837 (732)-661-2001 main (732)-661-2003 fax Sales@newarkwireworks.com

Distributed by:

Follow us:





